

工業配管用不銹鋼鋼管 / 大管徑配管用不銹鋼鋼管

Stainless Steel Pipes / Large Diameter Stainless Steel Pipes

JIS G3459, CNS 6331 / JIS G3468, CNS 13517

公稱直徑 Nominal Diameter		外徑 Outside Diameter (mm)	公稱厚度 Nominal Wall Thickness (mm)								其他通銷厚度 Other Common Thickness
A	B		JIS G3459, CNS 6331				JIS G3468, CNS 13517				
			SCH 5S	SCH 10S	SCH 20S	SCH 40	SCH 5S	SCH 10S	SCH 20S	SCH 40	
8	1/4	13.8	1.2	1.65	2.0	2.2	-	-	-	-	-
10	3/8	17.3	1.2	1.65	2.0	2.3	-	-	-	-	1.5/2.5
-	-	20.4*	-	-	-	-	-	-	-	-	2.0/2.5
15	1/2	21.7	1.65	2.1	2.5	2.8	-	-	-	-	2.0/3.0/3.2
-	-	26.4*	-	-	-	-	-	-	-	-	2.0/2.5
20	3/4	27.2	1.65	2.1	2.5	2.9	-	-	-	-	2.0/2.8/3.0/3.2
-	-	33.4*	-	-	-	-	-	-	-	-	2.0/2.5/3.0
25	1	34.0	1.65	2.8	3.0	3.4	-	-	-	-	2.0/2.5/3.5/4.0
32	1 1/4	42.7	1.65	2.8	3.0	3.6	-	-	-	-	2.0/2.5/3.5/4.0/4.5/5.0
40	1 1/2	48.6	1.65	2.8	3.0	3.7	-	-	-	-	1.5/2.0/2.5/3.5/4.0/4.5/5.0
50	2	60.5	1.65	2.8	3.5	3.9	-	-	-	-	2.0/2.5/3.0/4.0/4.5/5.0
65	2 1/2	76.3	2.1	3.0	3.5	5.2	-	-	-	-	2.0/2.5/4.0/5.0/5.5
80	3	89.1	2.1	3.0	4.0	5.5	-	-	-	-	2.0/2.5/3.5/4.5/5.0/6.0
90	3 1/2	101.6	2.1	3.0	4.0	5.7	-	-	-	-	2.0/2.5/3.5/5.0/6.0
100	4	114.3	2.1	3.0	4.0	6.0	-	-	-	-	2.0/2.5/3.5/4.5/5.0/6.5
125	5	139.8	2.8	3.4	5.0	6.6	-	-	-	-	2.5/3.0/3.5/4.0/5.5/6.0/6.5
150	6	165.2	2.8	3.4	5.0	7.1	2.8	3.4	5.0	7.1	3.0/3.5/4.0/5.5/6.0/6.5/7.0
200	8	216.3	2.8	4.0	6.5	8.2	2.8	4.0	6.5	8.2	3.0/3.5/4.5/5.0/6.0/7.0
250	10	267.4	3.4	4.0	6.5	9.3	3.4	4.0	6.5	9.3	3.0/3.5/4.5/6.0/7.0
300	12	318.5	4.0	4.5	6.5	10.3	4.0	4.5	6.5	10.3	3.0/3.5/5.0/6.0/7.0
350	14	355.6	-	-	-	11.1	4.0	5.0	8.0	11.1	6.0
400	16	406.4	-	-	-	12.7	4.5	5.0	8.0	12.7	4.0/6.0
450	18	457.2	-	-	-	14.3	4.5	5.0	8.0	14.3	-
500	20	508.0	-	-	-	15.1	5.0	5.5	9.5	15.1	-
550	22	558.8	-	-	-	15.9	5.0	5.5	9.5	15.9	-
600	24	609.6	-	-	-	17.5	5.5	6.5	9.5	17.5	-
650	26	660.4	-	-	-	18.9	5.5	8.0	12.7	-	-
700	28	711.2	-	-	-	-	5.5	8.0	12.7	-	-
750	30	762.0	-	-	-	-	6.5	8.0	12.7	-	-
800	32	812.8	-	-	-	-	-	8.0	12.7	-	-
850	34	863.6	-	-	-	-	-	8.0	12.7	-	-
900	36	914.4	-	-	-	-	-	8.0	12.7	-	-
1000	40	1016.0	-	-	-	-	-	9.5	14.3	-	-
備註 Remark			(1)上表以外之尺寸需求，由買賣雙方協議及最小批量限制。 Other nominal diameter and wall thickness subject to the approval of vendor and purchaser with MOQ requirement. (2)不銹鋼原料之化學成份：依據規範 ASTM A240。 (3)*表示為國內建築、水電用配管，厚度公差為±0.35mm。								