

一般配管用不銹鋼鋼管(壓接管)

Light Gauge Stainless Steel Tubes for Ordinary Piping

JIS G3448, CNS 13392

外徑 Outside Diameter (mm)	Su	13	20	25	30	40	50	60	75	80	100	125	150	200	250	300
	mm	15.88	22.22	28.58	34.0	42.7	48.6	60.5	76.3	89.1	114.3	139.8	165.2	216.3	267.4	318.5
厚度 Thickness (mm)		0.8	1.0	1.0	1.2	1.2	1.2	1.5	1.5	2.0	2.0	2.0	3.0	3.0	3.0	3.0

歐規不銹鋼鋼管

Welded Stainless Steel Tubes for Pressure Purposes

EN 10217-7

Thickness (mm) 外徑 Outside Diameter(mm)	1.0	1.2	1.5	1.6	2.0	2.3	2.5 2.6	3.0	3.2	3.5 3.6	4.0	5.0	5.5	6.0	6.5	7.1	8.0	9.0	10.0
10	□	□																	
12	◎	◎	◎	◎															
15	□	□	□	□	□														
16	◎	◎	◎	◎	◎														
17.2			△	△	△	△	△												
18 / 20	◎	◎	◎	◎	◎														
21.3		◎	◎	◎	◎	◎	◎	◎											
22	◎	◎	◎	◎	◎														
25	◎	◎	◎	◎	◎	◎	◎	◎											
26.9		◎	◎	◎	◎	◎	◎	◎											
28 / 30	◎	◎	◎	◎	◎	◎	◎	◎											
31.8 / 32	◎	◎	◎	◎	◎	◎	◎	◎											
33.7		◎	◎	◎	◎	◎	◎	◎	*	*	*								
35 / 38 / 38.1	◎	◎	◎	◎	◎	◎	◎	◎											
40	◎	◎	◎	◎	◎	◎	◎	◎											
42.4		◎	◎	◎	◎	◎	◎	◎	*	*	*	*							
44.5	◎	◎	◎	◎	◎	◎	◎	◎											
48.3		◎	◎	◎	◎	◎	◎	◎	*	*	*	*							
50.8 / 51		◎	◎	◎	◎	◎	◎	◎											
54 / 57		◎	◎	◎	◎	◎	◎	◎											
60.3		◎	◎	◎	◎	◎	◎	◎	*	*	*	*							
63.5		◎	◎	◎	◎	◎	◎	◎											
70		◎	◎	◎	◎	◎	◎	◎											
76.1			◎	◎	◎	◎	◎	◎	*	*	*	*	*						
88.9 / 101.6			◎	◎	◎	◎	◎	◎	*	*	*	*	*	*					
114.3			□	□	□	□	□	□	*	*	*	*	*	*					
139.7							△	△	*	*	*	*	*	*					
168.3								△	*	*	*	*	*	*	*	*			
219.1									*	*	*	*	*	*	*	*	*		
273																			
323.9-457																			
508																			

備註 Remark	(1)橘色區塊(Orange Mark)：無退火規格(Non-Annealed Spec.) (2)表面(Finish)：(*：Polish#180)；(△：Polish#180/#320)；(□：Polish#180/#320/#400)； (◎：Polish#180/#320/#400/#600) (3)冷軋用料(CR Material)：厚度(Thickness)1.0~3.0mm (4)熱軋用料(HR Material)：厚度(Thickness)2.0~10.0mm (5)外徑(Outside Diameter) ≤ 114.3mm · 亦可生產 STM A554規範(Also available by ASTM A554)
--------------	--