

機械構造用不銹鋼鋼管

Stainless Steel Tubing for Mechanical and Structural Purposes

ASTM A554, JIS G3446, CNS 5802

外徑 Outside Diameter	厚度 Thickness		0.8	0.9	1.0	1.2	1.25	1.5	1.6 1.65	2.0	2.11	2.5	3.0 3.05	4.0	5.0
	in	mm	0.031	0.035	0.039	0.047	0.049	0.059	0.063 0.065	0.079	0.083	0.098	0.118 0.120	0.157	0.197
3/8 / -	9.5/10		□	□	□	□	□								
- / 1/2	12/12.7		◎	◎	◎	◎	◎	◎	◎						
-	14/15		◎	◎	◎	◎	◎	◎	◎	◎					
5/8	15.9/16		◎	◎	◎	◎	◎	◎	◎	◎					
-	18		◎	◎	◎	◎	◎	◎	◎	◎	◎				
3/4	19/19.05		◎	◎	◎	◎	◎	◎	◎	◎	◎				
-	20		◎	◎	◎	◎	◎	◎	◎	◎	◎				
-	21.3		◎	◎	◎	◎	◎	◎	◎	◎	◎	◎			
7/8	22/22.2		◎	◎	◎	◎	◎	◎	◎	◎	◎				
1	25/25.4		◎	◎	◎	◎	◎	◎	◎	◎	◎	◎			
-	26.9					◎	◎	◎	◎	◎	◎	◎	◎		
1 1/8	28/28.6		◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎		
-	30		◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎		
1 1/4	31.75/31.8/32		◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎		
-	33.7					◎	◎	◎	◎	◎	◎	◎	◎	*	*
-	35		◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎		
1 1/2	38/38.1		◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎		
- / 1 5/8	40/41.28			◎	◎	◎	◎	◎	◎	◎	◎	◎	◎		
-	42					◎	◎	◎	◎	◎	◎	◎	◎		
-	42.4					◎	◎	◎	◎	◎	◎	◎	◎	*	*
1 3/4	44.45/44.5/45			◎	◎	◎	◎	◎	◎	◎	◎	◎	◎		
1.9	48.26/48.3			◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	*	*
- / 2	50/50.8/51			◎	◎	◎	◎	◎	◎	◎	◎	◎	◎		
2 1/8 / 2 1/4	54/57				◎	◎	◎	◎	◎	◎	◎	◎	◎		
-	60.3					◎	◎	◎	◎	◎	◎	◎	◎	*	*
2 1/2 / 2 3/4	63.5/70					◎	◎	◎	◎	◎	◎	◎	◎		
3	76.1/76.2					◎	◎	◎	◎	◎	◎	◎	◎	*	*
3 1/2 / 4	88.9/101.6							◎	◎	◎	◎	◎	◎	*	*
4 1/2	114.3							□	□	□	□	□	□	*	*
5	127							△	△	△	△	△	△		
5 1/2	139.7											△	△	*	*
6	152.4							△	△	△	△	△	△		
-	168.3											△	△	*	*
8	203.2									△	△	△	△		
備註 Remark	(1)Marking : 產品規格(Product Spec.) (2)表面(Finish) : (*: Polish#180); (△: Polish#180/#320); (□: Polish#180/#320/#400); (◎: Polish#180/#320/#400/#600)														

食品衛生用不銹鋼鋼管 / 鍋爐熱交換器用不銹鋼鋼管

Welded Stainless Steel Sanitary Tubing, Tubes for Boiler, Heat-Exchanger & General Service Tubing

ASTM A249/A269/A270, AS 1528.1, JIS G3447/G3463, CNS 6668/7383, EN10357

外徑 Outside Diameter	厚度 Thickness	in	1/2	5/8	3/4	7/8	1	1 1/4	-	1 1/2	2	2 1/2	3	3 1/2	4	4 1/2
		mm	12.7	15.9	19 19.05	22.2	25.4 (25)	31.8 (32)	35	38.1 (38)	50.8 (51)	63.5	76.2	88.9	101.6	114.3
1.2 / 1.25	-/18	Gauge	*	*	*	*	*	*	*	*	*	*	-	-	-	-
1.50	-		*	*	*	*	*	*	*	*	*	*	*	*	*	-
1.60/1.65	-/16		*	*	*	*	*	*	*	*	*	*	*	*	*	-
2.00/2.11	-/14		-	*	*	*	*	*	*	*	*	*	*	*	*	*
備註 Remark	(1)Marking : Product Spec. for ASTM A249/A270, AS 1528.1, JIS G3447/G3463, CNS 6668/7383, EN10357 (2) * : Product Spec. for ASTM A269															